



Technical data

| | |
|--------------------------------------|------------------------|
| Wall sleeve dimensions (WxDxH) | 295 x 208 x 140 mm |
| Cover dimensions (WxDxH) | 363 x 9,5 x 209 mm |
| Weight (incl. accessories/packaging) | approx. 2,8 kg |
| Material | Plastic |
| Material cover | Stainless steel 1.4301 |
| duct connection | BORA Ecotube |

Product description

- Optimal extraction performance with the lowest possible noise level
- Purely mechanical operation
- Two flaps with EPS insulation
- Outstanding insulation value
- Integrated water drainage to the outside
- Low pressure resistance during operation
- Optimised opening pressure
- UV resistant materials
- 100% tight without additional taping
- Including required Ecotube seals

Scope of delivery

- UEBF BORA 3box
- 6 x mounting wedges made of EPS
- installation instructions
- 1 x flat seal EFD
- 1 x Ecotube shallow duct with a bar 375mm EFS375

Accessories

- BORA 3box wall sleeve safety guard UEBFES

Product- and planning instructions

- Wall opening: 310 x 155 mm
- Ecotube duct connection with a shallow sleeve form
- Suitable for a minimum wall depth of 200 mm
- The wall sleeve must not be installed rotated 180°, vertical or with the exhaust opening facing downwards
- The safety guard UEBFES is to be used if the distance between the fan exhaust opening and the wall sleeve exhaust opening is less than 900 mm in the case of a straight exhaust duct
- Must expel air in a straight line regardless of the weather conditions (min. 300 mm)