

**technical data**

Maximum gas cooktop power	3,9 kW
Supply voltage	220 - 240 V
Frequency	50/60 Hz
Maximum power consumption	3.9 kW
Maximum power rating	1.1 W
Minimum fuse protection	1 x 0.5 A
Power levels	Freely adjustable
Weight (incl. accessories/packaging)	9.7 kg
Surface material	SCHOTT CERAN®
Power supply cable	1 m, Schuko plug types E + F
high-power burner	2900 W
Dimensions (WxDxH)	340 x 515 x 56 mm

**Product description**

- Compact size
- Minimalistic design
- Modular system
- 2-flame gas cooktop
- Dishwasher-safe pan supports
- Easy installation
- Different installation options
- Top-quality design
- Extended warranty free of charge
- Gas safety function

**Scope of delivery**

- CG11 gas glass ceramic cooktop
- Brushed stainless steel knob
- mounting straps
- sealing tape
- Flexible gas connection for simple installation, length 500 mm, 1/2" outer thread
- glass ceramic scraper
- height adjustment plate set
- operating and installation instructions

**product- and planning instructions**

- The CKAEG air inlet grille cannot be combined with the gas cooktop
- Please note the local regulations and connection requirements applicable to gas cooktops!
- When combining two CG11 gas glass ceramic cooktops and a CKASE cooktop extractor, two CKAABO cover plates must be additionally ordered as an air baffle.