



technical data

Multiphase supply voltage	380 - 415 V 2N/3N
Single-phase supply voltage	220 - 240 V
Frequency	50/60 Hz
Maximum power consumption	7,6 kW (4,4 kW)
Three-phase power supply/fuse protection	3 x 16 A
Two-phase power supply/fuse protection	2 x 16 A
Single-phase power supply/fuse protection	1 x 32 A (1 x 20 A)
Dimensions (WxDxH)	830 x 515 x 198 mm
Weight (incl. accessories/packaging)	Approx. 25 kg
Surface material	SCHOTT CERAN®
Cooktop extractor power levels	1 - 9, P
Cooktop power levels	1 - 9, P
duct connection	BORA Ecotube
Size of front cooking zone	230 x 230 mm
Size of rear cooking zone	230 x 230 mm
Front cooking zone output	2100 W
Rear cooking zone output	2100 W
Front cooking zone power setting output	3700 W
Rear cooking zone power setting output	3700 W

Product description

- Minimum volume
- Simple cleaning
- Genuine stainless steel grease filter
- Oversized 4 24 cooking surface
- Oversized surface induction cooking zones
- Maximum storage space
- Compact size
- Automatic extractor control
- Variable heat retention function
- childproofing feature

Scope of delivery

- Surface induction glass ceramic cooktop with BFIA cooktop extractor
- air inlet nozzle
- stainless steel grease filter
- BLAVH horizontal exhaust air extension
- mounting straps
- sealing tape
- glass ceramic scraper
- cable routing clips
- height adjustment plate set
- operating and installation instructions

Accessories

- BFF stainless steel grease filter
- BFIED air inlet nozzle
- BUSU recirculation conversion set
- UDB25 sealing tape
- BKR830 cooktop frame
- BLAVH1 exhaust air duct extension

product- and planning instructions

- The connection cable must be provided at the installation site
- Front power socket
- Use of an additional duct fan is possible for very long or complex exhaust air channels
- Please note that induction-compatible cookware must be used on induction cooktops
- The Basic cooktop extractor system can be combined with all BORA sockets