



technical data

Supply voltage	220 - 240 V
Frequency	50/60 Hz
Maximum power consumption	3.7 kW
Maximum power rating	3.7 kW
Minimum fuse protection	1 x 16 A
Power levels	1 - 9, P
Weight (incl. accessories/packaging)	7.2 kg
Surface material	SCHOTT CERAN®
Power supply cable	1.5 m (L, N, PE)
Dimensions (WxDxH)	340 x 515 x 52 mm
Front cooking zone dimensions	230 x 207 mm
Front cooking zone power	2100 W
Front cooking zone power setting	3700 W
Back cooking zone dimensions	230 x 207 mm
Back cooking zone power	2100 W
Back cooking zone power setting	3700 W

Product description

- automatic cut-off
- Pause function
- automatic heat up function
- warming function
- Timer function
- residual heat display
- power setting
- pan size recognition
- childproofing feature
- bridging function

Add-on product description

- Please note that induction-compatible cookware must be used on induction cooktops
- Make sure that the area below the induction cooktop is sufficiently ventilated – opening cross-section > 50 cm²

Scope of delivery

- CFI11 surface induction glass ceramic cooktop
- mounting straps
- sealing tape
- glass ceramic scraper
- height adjustment plate set
- operating and installation instructions

Accessories

- UGPI1 grill pan