


CKIW


BORA Classic induction glass ceramic wok











technical data

Supply voltage	220 - 240 V
Frequency	50/60 Hz
Maximum power consumption	3.0 kW
Maximum power rating	3.0 kW
Minimum fuse protection	1 x 16 A
Power supply cable length	1,5 m
Dimensions (WxDxH)	327 x 515 x 116 mm
Weight (incl. accessories/packaging)	9.8 kg
Surface material	SCHOTT CERAN®
Cooktop power levels	1 - 9, P
Size of cooking zone	Ø 250 mm
Cooking zone output	2400 W
Cooking zone power setting output	3000 W

Product description

- Variable heat retention function
- childproofing feature
- Cooking zone timers
- Timer
- Pause function
- Demo mode
- automatic heat up function
- pan size recognition
- residual heat display
- Increased resistance against breakage

- Scope of delivery
 Induction glass ceramic wok CKIW
- glass ceramic scraper
- mounting straps
- · height adjustment plate set

Accessories

HIW1 BORA induction wok

product- and planning instructions

- Due to the installation height of 116 mm, the appliance cannot be installed over the exhaust ducting.
- Ensure sufficient ventilation of the area below the cooktop.
- Glass ceramic mould: Diameter 250 mm
- Use a wok that loses its magnetic properties when the temperature rises (overheating protection). We recommend the use of the wok available from us