



### technical data

Supply voltage	220 - 240 V
Frequency	50/60 Hz
Maximum power consumption	3.0 kW
Maximum power rating	3.0 kW
Minimum fuse protection	1 x 16 A
Power levels	1 - 9, P
Cooking zone size	Ø 250 mm
Weight (incl. accessories/packaging)	9.0 kg
Cooking zone power	2400 W
Surface material	SCHOTT CERAN®
Cooking zone power setting	3000 W
Power supply cable	1.5 m (L, N, PE)
Dimensions (WxDxH)	340 x 515 x 112 mm

### Product description

- Minimalistic design
- Compact size
- Modular system
- childproofing feature
- Cooking zone timers
- Pause function
- automatic heat up function
- pan size recognition
- Increased resistance against breakage
- residual heat display

### Scope of delivery

- CIW1 induction glass ceramic wok cooktop
- mounting straps
- sealing tape
- glass ceramic scraper
- height adjustment plate set
- operating and installation instructions

### Accessories

- HIW1 induction wok, Controlinduc®, stainless steel, Ø 360 mm

### product- and planning instructions

- If the CIW1 induction glass ceramic wok cooktop is used, the groove dimensions must be increased to 7 mm for flush installation.
- The installation height of 112 mm means that the device cannot be installed over the exhaust ducting. Installation is therefore only possible to the left of the extractor.
- Glass ceramic mould: Diameter 250 mm
- A wok must be used that loses its magnetic properties when the temperature rises (overheating protection). We recommend using the BORA induction wok.
- Make sure that the area below the induction cooktop is sufficiently ventilated – opening cross-section > 50 cm<sup>2</sup>