



### Technical data

Wall sleeve dimensions (WxDxH)	Ø 170 x 145 - 165 mm
Cover dimensions (WxDxH)	234 x 8 x 234 mm
Weight (incl. accessories/packaging)	Approx. 1.5 kg
Material	Plastic
Material cover	Stainless steel 1.4301
duct connection	BORA Ecotube

### Product description

- Installation in thin walls
- Purely mechanical operation
- One flap with EPS insulation
- Optimised opening pressure
- Reduced installation effort
- Shortenable sleeve design
- Plaster cover
- Integrated water drainage to the outside
- Low pressure resistance during operation
- UV resistant materials

### Scope of delivery

- BORA 3box UEBRK
- Plaster cover
- installation instructions
- 1 x round seal ERD

### Accessories

- BORA 3box wall sleeve round safety guard UEBRES

### Product- and planning instructions

- Core hole diameter Ø180 mm
- Duct connection Ecotube with a round bushing design
- Bushing length 45 mm (can be shortened by 20 mm)
- Suitable for a minimum wall depth of 145 mm
- The wall sleeve must not be installed rotated 180°, vertical or with the exhaust opening facing downwards
- The safety guard UEBRES is to be used if the distance between the fan exhaust opening and the wall sleeve exhaust opening is less than 900 mm in the case of a straight exhaust duct
- Must expel air in a straight line regardless of the weather conditions (min. 300 mm)