



technical data

Supply voltage	220 - 240 V
Frequency	50/60 Hz
Maximum power consumption	3.7 kW
Maximum power rating	3.7 kW
Minimum fuse protection	1 x 16 A
Power levels	1 - 9, P
Weight (incl. accessories/packaging)	8.1 kg
Surface material	SCHOTT CERAN®
Back cooking zone dimensions	230 x 230 mm
Power supply cable	1.5 m (L, N, PE)
Dimensions (WxDxH)	370 x 540 x 52 mm
Front cooking zone dimensions	230 x 230 mm
Front cooking zone power	2100 W
Back cooking zone power	2100 W
Front cooking zone power setting	3700 W
Back cooking zone power setting	3700 W

Product description

- Intelligent control knob
- Oversized 4 24 cooking surface
- Oversized surface induction cooking zones
- Performance level display on the cooktop
- Variable heat retention function
- childproofing feature
- bridging function
- Cooking zone timers
- Timer
- Demo mode

Scope of delivery

- PKFI11 surface induction glass ceramic cooktop
- 2 x control knobs
- 2 x connection cables for the control knobs
- Connection cable to the extractor
- operating and installation instructions
- mounting straps
- glass ceramic scraper
- height adjustment plate set

product- and planning instructions

- Rotation by 180° possible during installation
- Please note that induction-compatible cookware must be used on induction cooktops
- Make sure that the area below the induction cooktop is sufficiently ventilated