



technical data

Maximum air volume	647 m ³ /h
Supply voltage	380 - 415 V 2N/3N
Supply voltage	220 - 240 V
Frequency	50 Hz
Maximum power consumption	7.0 kW
Fuse protection / power supply	3 x 16 A
Fuse protection / power supply	2 x 16 A
Fuse protection / power supply	1 x 32 A
Dimensions (WxDxH)	760 x 515 x 196 mm
Weight (incl. accessories/packaging)	25 kg
Connection on the exhaust side	BORA Ecotube
Surface material	SCHOTT CERAN®
Power levels	1, 2, P
Power levels	1 - 9, P
Back cooking zone dimensions	Ø 140 mm
Front cooking zone dimensions	Ø 210 mm
Front cooking zone power	2300 W
Back cooking zone power	1200 W
Front cooking zone power setting	3000 W
Maximum static pressure	339 Pa

Product description

- Minimum volume
- Super fast parboiling
- Simple cleaning
- Genuine stainless steel grease filter
- Oversized 4 24 cooking surface
- Compact size
- Free choice of cooktop
- automatic heat up function
- childproofing feature
- Cooking zone timers

Scope of delivery

- Hyper glass ceramic cooktop with BHA cooktop extractor
- stainless steel grease filter
- BLAVH horizontal exhaust air extension
- mounting straps
- sealing tape
- glass ceramic scraper
- cable routing clips
- height adjustment plate set
- operating and installation instructions

Accessories

- BFF stainless steel grease filter
- BFIED air inlet nozzle
- BUSU recirculation conversion set
- UDB25 sealing tape
- BKR760 cooktop frame
- BLAVH1 exhaust air duct extension

product- and planning instructions

- Basic cooktop extractor system can be combined with the sockets USTF, USTE, USTJ, USTG and USTL
- The connection cable must be provided at the installation site
- Front power socket
- Max. exhaust channel length: 6 m