

## ES Etiquetado de eficiencia energética PL540E

Product description		
Professional cooktop extractor system with ULS25 plinth fan	PL540E	
Operating mode	Exhaust air	
Energy consumption	Value	EN standard
Annual energy consumption ( $AEC_{hood}$ )	26 kWh/a	61591
Energy efficiency class	A++	61591
Flow volume		
Fluid dynamic efficiency ( $FDE_{hood}$ )	39.4	61591
Fluid dynamic efficiency class	A	61591
Lighting		
Lighting efficiency ( $LE_{hood}$ )	* lx/Watt	*
Lighting efficiency class	*	*
Grease filtering		
Level 9 maximum ( $GFE_{hood}$ )	50%	61591
Class level 9 normal	F	61591
Flow volume		
Air flow level 1 minimum	232 m <sup>3</sup> /h	61591
Air flow level 9 maximum ( $Q_{max}$ )	626 m <sup>3</sup> /h	61591
Sound power level		
Level 1 minimum	44 dB(A)	60704-2-13
Level 9 maximum	67 dB(A)	60704-2-13
Sound pressure level (additional details)		
Level 1 minimum	32 dB(A)	**
Level 9 maximum	54 dB(A)	**
Details according to 66/2014		
Power consumption in off mode ( $P_o$ )	0 W	61591
Time increase factor	0.6	61591
Energy efficiency index ( $EEl_{hood}$ )	32	61591
Air flow rate at the best efficiency point ( $Q_{BEP}$ )	297 m <sup>3</sup> /h	61591
Pressure at the best efficiency point ( $P_{BEP}$ )	548 Pa	61591
Electric power input at the best efficiency point ( $W_{BEP}$ )	114.7 W	61591

Especificaciones del etiquetado de eficiencia energética

\* Esta posición no afecta a este producto.

\*\* El nivel de presión acústica se determinó a 1 m de distancia (descenso del nivel en función de la distancia) sobre la base de los niveles de potencia acústica de acuerdo a la norma EN 60704-2-13.