



technical data

Power levels	1 - 9, P
Connection on the exhaust side	BORA Ecotube
Supply voltage	220 - 240 V
Frequency	50/60 Hz
Maximum power consumption	700 W
Power supply cable	2 m
Dimensions (WxDxH)	482 x 540 x 176 mm
Weight (incl. accessories/packaging)	9.25 kg

Product description

- Intelligent control knob
- Automatic cover flap
- Minimum volume
- Simple cleaning
- Integrated grease drip pan
- Genuine stainless steel grease filter
- Modular system
- Automatic extractor control
- Maximum storage space
- Demo mode

Scope of delivery

- PKA cooktop extractor with integrated 90° bend
- Duct element straight (EFD seal required)
- Control knob
- cover flap
- stainless steel grease filter
- Filter tray
- Maintenance tray
- CAT 5 communication cable
- Universal control unit
- connection cable for the control knob
- operating and installation instructions
- height adjustment plate set
- Mounting clamps
- Power supply cable with type E + F plugs
- Ecotube seal flat EFD

Accessories

- PKA1FF stainless steel grease filter
- PKA1VK cover flap
- PKA1FW filter tray
- UNLI type I power supply cable (AUS)
- UNLJ type J power supply cable (CH)
- UNLG type G power supply cable (GB-IE)

product- and planning instructions

- Suitable for use as a recirculation or exhaust system
- Can be combined with all BORA Professional cooktops and BORA Universal fan modules
- In the event of an exhaust channel of more than 6 m in length or significant pressure losses, an additional Universal fan module must be used
- The worktop height can be adjusted as necessary
- Worktop depth: ≥ 700 mm (in conjunction with the straight duct element ≥ 650 mm)
- Airflow possible to the right or left
- Fan can be positioned in the plinth area as a result of the low installation height (100 mm) (when using the ULS plinth fan only)
- Installation type: flush or surface-mounted
- Universal control unit as central connection point can be simply and compactly positioned in the plinth area
- The extractor and Universal control unit are connected by a CAT 5 communication cable
- The drawers and/or shelves in the floor unit must be removable for maintenance and cleaning purposes
- The BORA Ecotube duct system is optimally tailored to the BORA cooktop extractors and guarantees 100% functionality and optimum performance
- Professional cooktop extractor system can be combined with USTF, USTE, USTJ, USTG and USTL sockets

Installation option: BORA Pro cooktop-extractor with straight duct element

