



technical data

Supply voltage	220 - 240 V
Frequency	50/60 Hz
Maximum power consumption	3.0 kW
Maximum power rating	3.0 kW
Minimum fuse protection	1 x 16 A
Power levels	1 - 9, P
Cooking zone size	Ø 310 mm
Weight (incl. accessories/packaging)	9.5 kg
Cooking zone power	2400 W
Surface material	SCHOTT CERAN®
Cooking zone power setting	3000 W
Power supply cable	1.5 m (L, N, PE)
Dimensions (WxDxH)	370 x 540 x 128 mm

Product description

- Intelligent control knob
- Variable heat retention function
- childproofing feature
- Cooking zone timers
- Timer
- Pause function
- automatic heat up function
- Increased resistance against breakage
- Modular system
- Demo mode

Scope of delivery

- PKIW1 induction glass ceramic wok cooktop
- 2 x control knobs
- 2 x connection cables for the control knobs
- Connection cable to the extractor
- operating and installation instructions
- height adjustment plate set
- mounting straps
- glass ceramic scraper

Accessories

- HIW1 induction wok, Controlinduc®, stainless steel, Ø 360 mm

product- and planning instructions

- The installation height of 128 mm means that the device cannot be installed over the exhaust ducting
- Make sure that the area below the induction cooktop is sufficiently ventilated
- Wok recess diameter 310 mm
- Use a wok that loses its magnetic properties when the temperature rises (overheating protection). We recommend using the BORA induction wok.