



technical data

| | |
|---------------------------------------|---------------------------------|
| Supply voltage | 380 - 415 V 2N |
| Frequency | 50/60 Hz |
| Maximum power consumption | 4.4 kW |
| Maximum power rating | 4.4 kW |
| Minimum fuse protection | 2 x 16 A |
| Power levels | 1 - 9, (switching of 2/3 rings) |
| Weight (incl. accessories/packaging) | 8.7 kg |
| Surface material | SCHOTT CERAN® |
| Back cooking zone dimensions | Ø 120 / 200 mm |
| Power supply cable | 1.5 m (L1, L2, N, PE) |
| Number of cooking zone circuits front | 3 |
| Dimensions (WxDxH) | 370 x 540 x 73 mm |
| Front cooking zone dimensions | Ø 120 / 180 / 235 mm |
| Front cooking zone power | 800 / 1600 / 2500 W |
| Back cooking zone power | 800 / 1900 W |
| Number of cooking zone circuits rear | 2 |

Product description

- Intelligent control knob
- Oversized 4 24 cooking surface
- Variable heat retention function
- 2-ring switching
- 3-ring switching
- childproofing feature
- Cooking zone timers
- Timer
- Pause function
- Demo mode

Scope of delivery

- PKC32 HiLight glass ceramic cooktop
- 2 x control knobs
- 2 x connection cables for the control knobs
- Connection cable to the extractor
- operating and installation instructions
- mounting straps
- glass ceramic scraper
- height adjustment plate set

product- and planning instructions

- Rotation by 180° possible during installation
- Ensure sufficient ventilation of the area below the cooktop.