



technical data

Supply voltage	380 - 415 V 2N
Frequency	50/60 Hz
Maximum power consumption	5.1 kW
Maximum power rating	5.1 kW
Minimum fuse protection	2 x 16 A
Power supply cable length	1,5 m
Dimensions (WxDxH)	370 x 540 x 73 mm
Weight (incl. accessories/packaging)	8.9 kg
Surface material	SCHOTT CERAN®
Cooktop power levels	1 - 9, (switching of 2/3 rings/roaster)
Number of cooking zone circuits front	3
Number of cooking zone circuits rear	2
Size of front cooking zone	Ø 120 / 180 / 235 mm
Size of rear cooking zone	Ø 165 mm / 290 x 165 mm
Front cooking zone output	800 / 1600 / 2500 W
Rear cooking zone output	1500 W / 2600 W

Product description

- Intelligent control knob
- Variable heat retention function
- Roaster switching
- 3-ring switching
- childproofing feature
- Cooking zone timers
- Timer
- Pause function
- automatic heat up function
- Demo mode

Scope of delivery

- PKC3B HiLight glass ceramic cooktop
- 2 x control knobs
- 2 x connection cables for the control knobs
- Connection cable to the extractor
- operating and installation instructions
- mounting straps
- glass ceramic scraper
- height adjustment plate set

product- and planning instructions

- Rotation by 180° possible during installation
- Ensure sufficient ventilation of the area below the cooktop.