



technical data

Supply voltage	380 - 415 V 2 N
Frequency	50/60 Hz
Maximum power consumption	5.1 kW
Maximum power rating	5.1 kW
Minimum fuse protection	2 x 16 A
Power levels	1 - 9, (switching 2-ring/hyper)
Weight (incl. accessories/packaging)	8.7 kg
Surface material	SCHOTT CERAN®
Back cooking zone dimensions	Ø 120 / 200 mm
Power supply cable	1.5 m (L1, L2, N, PE)
Number of cooking zone circuits front	1
Dimensions (WxDxH)	370 x 540 x 73 mm
Front cooking zone dimensions	Ø 235 mm
Front cooking zone power	2100 W
Back cooking zone power	800 / 1900 W
Front cooking zone power setting	3200 W
Number of cooking zone circuits rear	2

Product description

- Intelligent control knob
- Oversized 4 24 cooking surface
- Variable heat retention function
- Super fast parboiling
- 2-ring switching
- childproofing feature
- Cooking zone timers
- Timer
- Pause function
- Demo mode

Scope of delivery

- PKCH2 Hyper glass ceramic cooktop
- 2 x control knobs
- 2 x connection cables for the control knobs
- Connection cable to the extractor
- operating and installation instructions
- mounting straps
- glass ceramic scraper
- height adjustment plate set

product- and planning instructions

- Rotation by 180° possible during installation
- Ensure sufficient ventilation of the area below the cooktop.