



technical data

| | |
|---|---------------------------------|
| Supply voltage | 380 - 415 V 2 N |
| Frequency | 50/60 Hz |
| Maximum power consumption | 5.1 kW |
| Maximum power rating | 5.1 kW |
| Minimum fuse protection | 2 x 16 A |
| Power supply cable length | 1,5 m |
| Dimensions (WxDxH) | 370 x 540 x 73 mm |
| Weight (incl. accessories/packaging) | 8.7 kg |
| Surface material | SCHOTT CERAN® |
| Cooktop power levels | 1 - 9, (switching 2-ring/Hyper) |
| Number of cooking zone circuits front | 1 |
| Number of cooking zone circuits rear | 2 |
| Size of front cooking zone | Ø 235 mm |
| Size of rear cooking zone | Ø 120 / 200 mm |
| Front cooking zone output | 2100 W |
| Rear cooking zone output | 800 / 1900 W |
| Front cooking zone power setting output | 3200 W |

Product description

- Intelligent control knob
- Variable heat retention function
- Super fast parboiling
- 2-ring switching
- childproofing feature
- Cooking zone timers
- Timer
- Pause function
- automatic heat up function
- Demo mode

Scope of delivery

- PKCH2 Hyper glass ceramic cooktop
- 2 x control knobs
- 2 x connection cables for the control knobs
- Connection cable to the extractor
- operating and installation instructions
- mounting straps
- glass ceramic scraper
- height adjustment plate set

product- and planning instructions

- Rotation by 180° possible during installation
- Ensure sufficient ventilation of the area below the cooktop.