



technical data

Supply voltage	380 - 415 V 2N
Temperature control range	70 - 250°C
Frequency	50/60 Hz
Maximum power consumption	4.8 kW
Maximum power rating	4.8 kW
Minimum fuse protection	2 x 16 A
Weight (incl. accessories/packaging)	15.8 kg
Surface material	Brushed stainless steel
Back cooking zone dimensions	295 x 230 mm
Power supply cable	1.5 m (L1, L2, N, PE)
Dimensions (WxDxH)	370 x 540 x 73 mm
Front cooking zone dimensions	295 x 230 mm
Front cooking zone power	2400 W
Back cooking zone power	2400 W
Heat retention level	150 - 230°C, 250°C (1 - 9, P)

Product description

- Intelligent control knob
- Accurate temperature control
- Accurate temperature display
- Rapid heating
- Stainless steel grill area with two cooking zones
- Designed for optimum cleaning
- Cleaning function
- childproofing feature
- bridging function
- Demo mode

Scope of delivery

- PKT11 Tepan stainless steel grill
- 2 x control knobs
- 2 x connection cables for the control knobs
- Connection cable to the extractor
- operating and installation instructions
- PTTS1 Tepan scraper
- height adjustment plate set
- mounting straps

product- and planning instructions

- Make sure that the area below the Tepan cooktop is sufficiently ventilated.