



technical data

Supply voltage	380 - 415 V 2N
Frequency	50/60 Hz
Maximum power consumption	4.8 kW
Maximum power rating	4.8 kW
Minimum fuse protection	2 x 16 A
Power supply cable length	1,5 m
Dimensions (WxDxH)	370 x 540 x 73 mm
Weight (incl. accessories/packaging)	15.8 kg
Surface material	Brushed stainless steel
Temperature control range (Power levels)	150 - 230 °C, 250 °C (1 - 9, P)
Temperature control range	70 - 250 °C
Size of front cooking zone	295 x 230 mm
Size of rear cooking zone	295 x 230 mm
Bridged cooking zone dimensions	295 x 460 mm
Front cooking zone output	2400 W
Rear cooking zone output	2400 W
Bridged cooking zone power	4800 W

Product description

- Intelligent control knob
- Accurate temperature control
- Accurate temperature display
- Rapid heating
- Stainless steel grill area with two cooking zones
- Designed for optimum cleaning
- Cleaning function
- childproofing feature
- bridging function
- Demo mode

Scope of delivery

- PKT11 Tepan stainless steel grill
- 2 x control knobs
- 2 x connection cables for the control knobs
- Connection cable to the extractor
- operating and installation instructions
- PTTS1 Tepan scraper
- height adjustment plate set
- mounting straps

product- and planning instructions

- Ensure sufficient ventilation of the area below the cooktop.