



technical data

Supply voltage	220 - 240 V
Frequency	50 Hz
Power consumption	149 W
Current consumption	1.26 A
Maximum ambient temperature	70 °C
Maximum flow volume	940 m ³ /h
Maximum static pressure	456 Pa
Dimensions (WxDxH)	385 x 155 x 410 mm
Weight (excluding accessories/packaging)	16.5 kg
Casing material	Galvanized steel / stainless steel
Duct connection dimensions	Ø150 mm
Connection cable	10 m
control line	10 m

Product description

- Energy-saving fan with EC technology
- Complete BORA system

Scope of delivery

- ULA external wall fan
- Telescopic installation duct with integrated backflow trap
- Air repellent rail
- installation instructions
- Empty duct Ø 40 mm x 400 mm for cable passage
- sealing tape
- 1,25 m EPDM sealing tape

Accessories

- Universal extension of UVNLE10 mains cable EC 10 m
- Universal extension of UVSLE10 control line EC 10 m

product- and planning instructions

- In case of an exhaust channel of more than 6 m in length or significant pressure losses, the external wall fan must be supplemented with an additional Universal fan module
- If there are two fan components in one exhaust air duct system, a minimum distance of 3 m must be observed between these two fans
- A minimum downward clearance of 40 cm is required for the outflow
- For installation on the outside of the building
- Suitable for wall thicknesses of 280 mm to 490 mm
- If required, a KG duct with Ø 200 mm should be pre-installed in the external wall
- Air outlet downward
- Fixing elements must be provided at the installation site