



### technical data

Supply voltage	220 - 240 V
Frequency	50 Hz
Power consumption	206 W
Current consumption	1.66 A
Maximum ambient temperature	70°C
Maximum flow volume	1007 m <sup>3</sup> /h
Maximum static pressure	608 Pa
Dimensions (WxDxH)	390 x 500 x 280 mm
Weight (excluding accessories/packaging)	16.5 kg
Casing material	Galvanized steel / stainless steel
Duct connection dimensions	Ø 150-155 mm
Connection cable	10 m
control line	10 m

### Product description

- Energy-saving fan with EC technology
- Complete BORA system

### Scope of delivery

- ULZ tiled roof fan
- Fabric tube with backflow tap
- installation instructions

### Accessories

- Universal extension of UVNLE10 mains cable EC 10 m
- Universal extension of UVSLE10 control line EC 10 m

### product- and planning instructions

- In case of an exhaust channel of more than 6 m in length or significant pressure losses, the tiled roof fan must be supplemented with an additional Universal fan module
- If there are two fan components in one exhaust air duct system, a minimum distance of 3 m must be observed between these two fans
- For installation on a tiled roof with a roof slope of at least 10°
- The fully flexible fabric tube on the fan can be stretched by a maximum of 400 mm from the surface-mounted plate to the inner side of the building
- Air outlet downward
- A condensation separator must be installed, if necessary
- Fixing elements must be provided at the installation site