

EN PKA3 / PKA3AB product information sheet



PKA3


Pro cooktop extractor



PKA3AB

Pro cooktop extractor, All Black

General product information:

Product:	Cooktop extractor and central unit of the modular cooktop extractor system BORA Professional 3.0; depending on whether an exhaust air or recirculation model is chosen, further components (e.g. fan, silencer, odour filter, ducting) complete the extractor; can be combined with different cooktops
Product highlights:	Intuitive control knob with analogue/digital operation (knob ring + touch surface), automatic cover flap for opening and closing the air inlet opening.
Minimum installation dimensions: (1 extractor, 2 cooktops)	Kitchen unit with a min. width of 90 cm
Safety and warning information:	See operating and installation instructions
Energy efficiency class:	 (applies to the exhaust air model)

PKA3/PKA3AB

Pro cooktop extractor (...All Black)

Technical data

Supply voltage	220-240 V
Frequency	50/60 Hz
Maximum power consumption	550 W
Mains supply cable length	2 m
Dimensions (width × depth × height)	482 × 540 × 176 mm
Weight (incl. accessories/packaging)	9.25 kg
Surface material	Stainless steel 1.4016
Cooktop extractor power levels	1-9, P
Duct connection	BORA Ecotube

Product description

- Modular system
- Intuitive control knob
- Automatic cover flap
- Integrated drip tray
- Stainless steel grease filter
- Central components for the entire system

Functions

- Automatic extractor function
- Automatic after-run
- Power setting
- Filter service life and filter service display (recirculation only)
- Cleaning function
- Short-time timer
- Super simple mode

Safety features

Child lock, safety shut-down, anti-trap protection

Scope of delivery

Pro cooktop extractor PKA3/PKA3AB with integrated 90° bend, straight duct piece (moulded part with a shallow sleeve form), control knob, cover flap, stainless steel grease filter, filter tray, maintenance tray, CAT 5 communication cable, universal control unit, control knob connection cable, mains supply cable with E + F plugs, operating and installation instructions, installation accessories

Accessories

Stainless steel grease filter PKA1FF, cover flap PKA1VK/PKA1VKAB, filter tray PKA1FW, mains supply cable type I UNLI (AUS) / type J UNLJ (CH) / type G UNLG (GB-IE) / type B UNLB (PH) / type H UNLH (IL)

Product and planning information

- Suitable for use as a recirculation or exhaust system
- Suitable for use with all BORA Professional 3.0 cooktops
- Up to 2 cooktops can be connected to each cooktop extractor
- Suitable for use with all BORA universal fans
- Long or complex exhaust channels possible using an additional fan module
- Customisable worktop height
- Worktop depth ≥ 700 mm (with the straight duct element ≥ 650 mm)
- Flush installation or surface mounting possible
- Air channelling possible to the right or left
- Low installation height (100 mm) enables the fan to be positioned in the plinth area (ULS only)
- Control unit can be compactly positioned in the plinth area
- The appliance and control unit are connected via a CAT 5 communication cable
- The drawers/ shelves in the base unit must be removable (for maintenance/cleaning)
- Suitable for use with all BORA sockets

