

EN PUXA2 / PUXA2R product information sheet

High-gloss glass ceramic:



PUXA2

X Pure surface induction cooktop with integrated cooktop extractor – exhaust air


Matt glass ceramic:



PUXA2R

X Pure Rough surface induction cooktop with integrated cooktop extractor – exhaust air

General product information:

Product:	Compact cooktop extractor system – a combined cooktop and extractor system
Product highlights:	Effective cooktop extractor including stainless steel grease filter, cooktop with 4 very large induction cooking zones, intuitive touch controls, BORA Assist for simpler cooking experiences, wider range of functions with the BORA JOY app
Model:	Exhaust air system with BORA Ecotube duct connection
Minimum installation dimensions:	Kitchen unit with a min. width of 90 cm
Safety and warning information:	See operating and installation instructions
Energy efficiency class:	

PUXA2 / PUXA2R

X Pure surface induction cooktop with integrated cooktop extractor – exhaust air

Technical data

Multiphase supply voltage	380-415 V 2N/3N
Single-phase supply voltage	220-240 V
Frequency	50-60 Hz
Maximum power consumption	7600 W (4400 W / 3600 W)
3-phase fuse protection/power supply	3 × 16 A
2-phase fuse protection/power supply	2 × 16 A
1-phase fuse protection/power supply	1 × 32 A (1 × 20 A / 1 × 16 A)
Dimensions (width × depth × height)	830 × 515 × 199 mm
Weight (incl. accessories / packaging)	23.8 kg
Weight (net)	16.9 kg
Surface material	Glass ceramic
Cooktop extractor / cooktop power levels	1-9, P
Size of front cooking zones	230 × 230 mm
Size of rear cooking zones	230 × 230 mm
Front cooking zone output	2100 W
Rear cooking zone output	2100 W
Output of front cooking zones on power setting	3000 W
Output of rear cooking zones on power setting	3000 W
Duct connection	BORA Ecotube
Guaranteed availability period for software updates (from product discontinuation date)	5 years

Product description

- Connectivity and BORA Assist
- Intuitive tricolour sControl+ operating panel
- Oversized surface induction cooking zones
- Compact size
- Integrated grease drip tray
- Stainless steel grease filter

Functions

- BORA Assist function Fry
- Power setting
- Automatic extractor function
- Automatic after-run
- Pan size recognition
- Variable heat retention function
- Bridging function
- Cooking zone timer
- Pause function
- Short-time timer

Safety features

Child lock, control lock, cleaning lock, residual heat indicator, safety shut-down, overheating protection

Scope of delivery

Surface induction glass ceramic cooktop with integrated cooktop extractor – exhaust air PUXA2/PUXA2R, air inlet nozzle PUXED2, stainless steel grease filter, operating and installation instructions, installation accessories

Accessories

Stainless steel grease filter PUEF, air inlet nozzles PUXED2 and PUED2, sealing tape UDB25, cooktop frame KFR830AB, side frame USL515/USL515AB, grill pan for surface induction KWGPFI

Product and planning information

- The mains supply cable is to be provided on site
- Front power socket
- Flush installation or surface mounting possible
- Sufficient ventilation below the cooktop must be ensured
- The drawers or shelves in the base unit must be removable (for maintenance and cleaning)
- Suitable for use with all BORA sockets
- Not compatible with BORA universal fans
- When installation is complete, the appliance is to be sealed in using heat-resistant silicone sealant

